

PATENT APPLICANT

A.I.Rajasingham, 6024 Bradley Boulevard, Bethesda MD 20817. Tel: 301 229 0218.

TITLE OF INVENTION: Easy Ejector Seat with Skeletal Crash Safety Beam

CROSS REFERENCE TO RELATED APPLICATIONS: This application is a continuation in part of the application entitled “ Easy Ejector with skeletal crash safety beam” US S/N: 08/936,626 filed 9/24/97, US S/N 09/404,475, US S/N 09/435,830 and claims priority from US S/N: 08/936,626 filed 9/24/97, US S/N 09/404,475, US S/N 09/435,830, US S/N 60/195298, US S/N 60,226,570, EPO S/N 98948260.9-2306, EPO S/N 00203896.6.

STATEMENT REGARDING

FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT: Not Applicable

REFERENCE TO A MICRO FICHE APPENDIX: Not Applicable

BACKGROUND OF INVENTION

FIELD OF INVENTION

The present invention defines a means to incorporate in passenger motor vehicles, unique safety arrangements particularly for lateral or side impacts that provide energy absorption by the mass of the vehicle but decouple the passenger from the impact acceleration and deceleration that is provided by the mass of the vehicle, thereby protecting the passengers during such collisions. Moreover, the same arrangement synergistically provides utility in access, comfort and further safety in the operating position for passengers and the driver.

DESCRIPTION OF THE RELATED ART:

In the past safety of passengers was not always the priority in passenger vehicle design. In the evolution of motor vehicle design the structure moved from a chassis that held together the mechanical components of the vehicle – a structure that was then attached to a passenger compartment or to passenger seats.

1 The design of the structure was to hold together the working components of the vehicle – a critical aspect at the
2 time. Thereafter in more recent times right up to the present, Exo-skeletal designs have been the dominant
3 paradigm. Here rigid shells were constructed to hold both the mechanical components and the passengers in
4 fixed positions. However such fixed shell structures have had limited success in protecting passengers and
5 drivers when there are lateral collisions as passengers undergo the same impact related accelerations and
6 decelerations as the remaining parts of the vehicle, as space limitations don't allow for "crumple zones" as in
7 the case of impact protection for head on collisions. Passengers are particularly vulnerable to side impacts as
8 they cannot take preemptive measures as with head-on collisions where there is speed control and directional
9 control that is available. As vehicle speeds have increased substantially in the last several decades, these safety
10 considerations for passengers have become critical and urgent. Vehicle designers — particularly automobile
11 designers – have risen admirably to the task by incorporating myriads of devices and additions within the rigid
12 shell paradigm to minimize risk in the event of collisions. Such devices include restraints such as seat belts and
13 certain types of protective air bags. However, there are limits within the rigid shell paradigm for two reasons:
14 First, the energy of impact cannot be easily diverted away from passengers into the remaining mass of the
15 vehicle on impact. Second, the rigid shell needs to support high shear stresses on lateral impact and related
16 compressive loads to the passenger compartment of the vehicle a factor that can only be addressed with greater
17 mass of the vehicle that will impact its performance.

18 Another area of interest in passenger vehicles is to provide, in synergy with the above
19 contributions, utility and comfort of passengers and drivers and further synergistic head-on collision protection.

20 There are four areas of Background art that are related to the present invention. These
21 are: vehicles with sliding seats, safety arrangements addressing lateral impacts on passenger vehicles, air bags
22 and other shock absorbing devices, and miscellaneous safety devices for frontal impacts. None of the inventions
23 in these areas individually or collectively state or imply any aspects of the present invention. Moreover, none of
24 this Background art even addresses the issue of energy transfer away from the passengers to the mass of the
25 vehicle on impact and concurrently provide a mechanism for easy access to the vehicle with ejector seats. This
26 is despite the urgent need in the car industry for such safety and utility. Moreover the novelty of the present
27 invention is underscored as it provides solutions hitherto unidentified in a very large and competitive industry
28 that is acutely aware of these needs and is constantly in search of new solutions to them.

29
30 Sloan 3,071,407 (1963) describes a single rear bench seat (lines 4-45) – full length (C1-
31 L55), that can slide out of either side of the vehicle. It describes a door structure that may be attached to the seat
32 and slide across and through the passenger compartment of the vehicle as the seat slides out. This invention
33 does not state or imply any safety considerations in its structure, moreover such a bench seat on slides, in the
34 event of a lateral collision on the doors will focus the impact energy on the passengers and these passengers
35 will be the principal casualties as the mass of the vehicle slides away little harmed. This will be the case even in
36 the embodiment described where the doors are fixed to the seat and slides through the passenger compartment
37 with the seat. Moreover, it cannot be used in a front seat even for its limited functionality with doors fixed to the
38 seat as driving instrumentation (steering wheel etc) will not allow a door to slide through the compartment.
39 Finally it does not provide any comfort features for passengers over and above a bench seat. Mach 2,753,947

(1956) describes a sliding bench seat for the access of the engine of the vehicle it does not address the issue of safety of passengers or access utility. It is expected to perform similarly to Sloan in an impact on the doors or around the side profile of the passengers in the vehicle. Solomon 2,758,872 (1953) provides a sliding bench seat that goes through the doorway and for the same reasons as Sloan does not provide protection in side impacts or provide any comfort features over and above a bench seat. Cyphert 3,944,277 (1976) describes a seat mounted on a sliding platform that has a door at the end and protective walls around it. The arrangement being designed for the utility of the operator to reach points away from the body of the vehicle without dismounting the vehicle. This invention like Sloan does not state or imply any safety considerations in its use. Moreover there is no expressed or implied reference to the utility of mounting and dismounting the vehicle or for the comfort of the operator or the passengers except for the ability for the platform to move out to give the operator greater reach away from the vehicle body. Rees 5,213,300 (1993) describes internal design structure for slide arrangements that allow forward and backward movement of the passenger seats in vehicles. This like many other inventions prior to it relate to the structure of the slides to adjust the position of the seats for passenger comfort in the direction of motion of the vehicle.

All the above items of background art relate to sliding seats. None of the above background art related to sliding seats have stated or implied safety considerations. Moreover, none of them provide utility for mounting and dismounting a vehicle except for a bench seat that slides out on either side of the vehicle, or provide comfort features except for seating arrangement on a bench seat and in one of the above -- the lateral movement for convenience of the operator.

Maier US 2,148,950 (1939) provides a laterally braced passenger compartment that braces a rigid shell body of a vehicle. Barenyi 2,710,222 (1955) provides a stiffening for the bottom plate of a vehicle body. Catlin 5,660,428 (1997) provides a design for a rigid shell structure. Guertler 5,464,266 (1995) uses stiffening arrangements for the floor of the vehicle as a component of a rigid shell vehicle body. Masuda 5,671,968 (1968) describes a strengthened rigid shell for the passenger compartment. Oliver 4,533,172 (1985) describes a three part rigid shell structure for motor vehicles with the central section for passengers. Sinnhuber 5,000,509 (1991) describes an arrangement that transfers impact energy from lateral impacts to the rigid body of the vehicle but does so through rigid members that include elements in the seats. The seats have limited lateral movement and are not free to move independent of the vehicle body in the event of a collision, thereby placing the passengers on the direct path of the energy transfer. Maeda 4,512,604 (1985) describes a lateral brace for the seat arrangement of the vehicle within a rigid vehicle body structure thereby distributing the impact energy to other parts of the rigid body structure. Sacco 5,435,618 (1995) describes a lateral stiffening element that braces the rigid vehicle body in the region of the seats. Bhalsod 5,716,094 (1998) describes a pusher block that engages the seat in the event of a lateral impact thereby providing a rigid member between the rigid body structure and the seats that can transfer impact energy to the seats.

All of the above items of background art related to bracing a rigid body structure and provide stiffening mechanisms within the rigid shell structure to distribute energy of lateral impact. None of these items of background art provide mechanisms to transfer energy away from passengers in lateral impacts.

1 or provide other safety arrangements or provide utility for mounting and dismounting the vehicle or provide
2 comfort features for passengers in the operating position.

3
4 Baber 5,725,265 (1998) presents airbags for front and rear vehicle bumpers that deploy
5 on impact. Such devices cannot be implemented on the side of the vehicle as a deceleration zone is not available
6 under operating conditions as may be made available in the front and back of the vehicle. Moreover, as this
7 airbag deploys on impact it creates a deceleration zone by pushing its own vehicle away that may actually
8 increase the impulse forces acting on the passengers. Mercier 3,822,076 (1974) describes similar external
9 front and back airbags and uses probes that protrude from the vehicle at the front and back to deploy the
10 airbags. Such apparatus cannot be installed on the sides of the vehicle, as clearances are small. Stirling
11 5,131,703 (1992) describes a fluid filled chamber around the vehicle that will provide a deceleration zone on
12 impact – frontal rear or lateral. However this arrangement requires the deceleration zone to be present during
13 normal operating conditions that will reduce the maneuverability of vehicles if deployed on the sides of the
14 vehicle. Park 4,995,659 (1991) describes a gas filled chamber deployed around the vehicle. Such a chamber is
15 normally inflated under normal conditions and reduces maneuverability of the vehicle. Campbell 4,815,777
16 (1989) describes a bumper that can be deployed selectively by filling with gas. This bumper is effective when
17 extended only. It is not designed to be deployed when the vehicle is in motion, as it will reduce
18 maneuverability. Hartmann 5,810,427 (1998) describes a mechanism that transfers fluid from one airbag to
19 another on impact. The airbag that is deployed is normally in an extended position to absorb the impact energy
20 and provide the deceleration zone. However, such an extended airbag will reduce the maneuverability of the
21 vehicle. There is a literature (“Extended Bumper and Glass-Plastic glazing methods to reduce intrusion and
22 ejection in severe motor vehicle crashes”. C.C.Clark 1993. 26th Symposium on Automotive Technology and
23 Automation. Aachen Germany., “Airbag bumpers inflated just before the crash” C.C.Clark., William A. Young.
24 1994. SAE Technical Paper 941051., “The crash anticipating extended airbag bumper system”. C.C.Clark.1994.
25 Fourteenth International Technical Conference on the enhanced safety of vehicles. Munich Germany., “Airbags
26 as a means to reduce crash loads and intrusion, and increase intervehicular compatibility.” C.C.Clark. 1995.
27 International Conference on Pelvic and Lower extremity injuries-Proceedings Washington DC., Human
28 Transportation Fatalities and Protection against Rear and Side Crash Loads by the Airstop Restraint” Carl Clark
29 and Carl Blechschmidt. 1965. The Ninth Stapp Car Conference.) IDS, and background art on the construction
30 of external airbags including deployment proactively with radar or other devices. This entire literature is limited
31 to the use of proactive external airbags mounted on vehicles with rigid structures that include the passenger.
32 There is no reference in this literature to the proactive detection of impact explicitly or implicitly creating a
33 deceleration zone for passenger protection internally, relative to the vehicle as in the present invention.
34 Moreover, this literature is focussed on external airbags for front impact protection with for example rigid
35 penetration buffers to negotiate posts and trees, unlike the present invention which does not prescribe external
36 airbags for front impacts. Furthermore, as this literature describes external airbags without perforation shields
37 their implementability is questionable as, unlike internal airbags that are in relatively protected environments,
38 impact with external airbags often occurs with objects with sharp points and edges that are likely to perforate
39 the external airbags. The Present invention requires perforation shields for external airbags.

All the above items of background art relate to air bag devices for safety in vehicles. However, none of these references take the integrated approach of the present invention, as more fully explained below, which comprises proactive deployment of both internal and external air bags, together with sliding seat members and other devices. Moreover while the present invention can function even without the deployment of external airbags, either proactive or reactive, taken together these items provide protection for passengers which is more than the sum of the parts. Furthermore, none of the protection airbags disclosed, related to external air bags having protective perforation shields that further enhance their efficacy. Moreover none of these devices provide energy transferring mechanisms away from the passenger in a lateral impact or provide other safety features. Moreover they do not provide any utility features for passengers in mounting and dismounting the vehicle or provide comfort features to the passengers.

Perras 2,873,122 (1959) which describes an invention where upon a head-on collision the seat projects a curved protector around the passenger designed to protect the passenger. This curved protector retracts into the seat under normal operating conditions. It is not clear how effective such a mechanism will be as the acceleration of the passenger forward relative to the vehicle may precede that of curved protector's release from the seat. Satzinger 3,961,805 (1976) describes seat belts for frontal collisions that provide safety for vehicles. Such seat belts are in common use. However, they suffer from the drawback that they restrain the body of the passenger in the narrow regions covered by such belts which may cause injury as other parts of the body are not restrained. Moreover such belts are not popular, while in common use as the belts are in constant contact with the body- a factor that is not often relished. Pulling 3,981,520 (1976) describes an arrangement where that provides passenger movement and protection in frontal impacts. On impact the passenger moves in the vertical plane of motion to a more protected position while side firing airbags provide frontal protection. This system of deployment of airbags for frontal collision protection is similar to other frontal airbag systems. They are necessary as restraining systems during the collision but need to be retracted in conventional passenger compartments to give passengers access to their seats while mounting and dismounting the vehicle. Erickson 2,777,531 (1957) describes an invention that rotates the seat of the passenger thereby restraining and protecting the passenger on impact taking advantage of the inertia prior to impact to endow the passenger with rotational energy that changes the position of the seat. Such rotation can injure the passenger with impacts at present day passenger vehicle speeds.

All the above items of background art relate to frontal impact protection. None of these items provide a device that is normally deployed during operation, and provides a broad area of restraint across the body for the entire upper body, head and neck, without a need for changing the orientation of the passenger. Moreover none of these items provide any protection for side impacts or provide utility for mounting and dismounting the vehicle or for the comfort of the passengers in the operating position.

SUMMARY

In view of these prior references what would be useful is an arrangement that diverts the impact energy in lateral or side impacts away from the passengers to the remaining mass of the vehicle thereby protecting the passengers, and in the same arrangement provides utilitarian access to the vehicle, such utilitarian access making it possible to both install multi-element contoured surround seats for passengers and the driver,

1 and also a safety device for head-on collision protection that obviates the need for conventional seat belts and
2 front impact airbags. Moreover, it would be useful to have a synergistic structural arrangement for the vehicle
3 that targets strength of the vehicle to protect passengers while minimizing other massive elements in the vehicle.

4 The present invention includes these objects and advantages.

5 OBJECTS & ADVANTAGES

6 Some of the objects and advantages of the present invention are, to provide an
7 arrangement that diverts the impact energy in lateral or side impacts away from the passengers to the
8 remaining mass of the vehicle thereby protecting the passengers but decelerating the impacting object
9 with the remaining mass of the vehicle. Moreover the arrangement synergistically provides a means
10 for utilitarian easy access to the vehicle for passengers and drivers alike and allows the installation of
11 multi-element surround contoured seats for the comfort and protection of passengers. This
12 arrangement differs sharply from the Background art in that it does not simply offer to the impacting
13 body a reinforced rigid shell where the passenger is treated as part of this integral unit, but rather
14 provides selective and differential treatment of the mass of the passengers and driver of the vehicle
15 vis-à-vis the remaining mass of the vehicle. Furthermore the present invention differs sharply from the
16 Background art in that the resulting structure synergistically permits the installation of contoured
17 multi-element surround seats and a unique safety harness that protects passengers in head-on
18 collisions, both of which may not be implementable without the slide or other moving arrangements
19 for seats on either side of the vehicle in the present invention.

20 Another object and Advantage of the present invention is the gravity slide drive
21 and a related shock absorbing arrangement relative to the fixed body members of the vehicle ad the
22 terrain traversed by the vehicle, for my arrangement for which there is no counterpart in the
23 Background art. This allows further Utility and weight and energy saving in implementing the above
24 elements of the present invention.

25 Another Object and Advantage of the present invention includes External side
26 Airbags that differ sharply from the Background art in that for the first time they proactively create a
27 “Just in Time” deceleration zone both for the passenger relative to the vehicle and also for the vehicle
28 relative to the impacting body, for the lateral or side impact while not remaining in an extended
29 position under normal operating conditions of the vehicle.

30 Another Object and advantage of this invention is a perforation resistant shield
31 for external airbag protection that would reduce the probability of deployment failure. The
32 background art does not provide for this function in externally deploying airbags.

33 Another object and advantage of the present invention is a indo-skeletal structure
34 of the vehicle body that permits the energy transfer from the lateral or side impact through
35 compressive members to the body of the vehicle. Unlike the Background art this indo-skeletal
36 structure is designed to transfer energy to the body of the vehicle without transferring it to the
37 passengers and driver of the vehicle. The passengers are targeted for protection with “Safety zones”.

BRIEF DESCRIPTION OF DRAWINGS

Figure 1 is an illustration of a front elevation of a seating arrangements in a passenger vehicle. This figure is an illustration of the invention in the normal vehicle operating condition. The impacting body is represented on the left as still distant but advancing towards the above passenger vehicle.

Figure 2 is an illustration of the same vehicle arrangement as in Figure 1, except that the impacting object has advanced towards the passenger vehicle adequately to trigger the distance and velocity sensors.

Figure 3 is an illustration of the same vehicle as in Figures 1 and 2, except that the distance and velocity sensors have deployed the external Airbags. They may also provide delayed deployment of the internal Airbags.

Figure 4 is an illustration of the same vehicle as in Figures 1,2 and 3 except that the impacting object has made impact with deceleration and energy absorption provided by the External airbags and the shock absorbers and resisted by the mass of the vehicle through compression members as noted below. The Passengers and seats are free to move away from the impact on the secondary slides as the internal Airbag deploys, pushing out the Primary slide on the side away from the impact.

Figures 1D, 2D, 3D and 4D illustrate an alternative embodiment with the shock absorbers mounted internal to the protector shield.

Figures 1C, 2C, 3C and 4C illustrate an alternative embodiment that has an auxiliary beam mounted behind the seat with a high section of the central member of the skeletal structure behind the seat to abut the auxiliary beam.

Figures 1B, 2B, 3B and 4B illustrate an alternative embodiment with a center console.

Figures 1F, 2F, 3F and 4F illustrate an alternative embodiment with a center console that is crushable and as a result decreases the need for the ejection of the passenger on the further side of the vehicle at impact.

Figures 1G, 2G, 3G and 4G illustrate an alternative embodiment with center airbags that are a part of a passive airbag system to protect passengers during lateral impact by absorbing some of the impact energy but more importantly providing a means to inflate head and neck protection airbags and other anatomical micro airbags mounted in the vicinity of the human body. This particular embodiment has a crushable center console as well.

Figure 5 and 6 is an illustration of the seating arrangement as used for loading and unloading passengers and driver. Figure 5 represents the open position and Figure 6 represents the closed position.

Figures 5A and 6A illustrate an embodiment of the current invention with the protector shield/shock absorbers/external airbag hinging down to support the primary slide. A useful feature for larger vehicles with more than a single seat on each side.

Figures 7-9 is an illustration of the Gravity slide drive that may be embodied in the invention. Figure 7 is an illustration of the Gravity Slide drive at the end of the unload cycle for passengers. Figure 8 is an illustration of the Gravity slide drive at the beginning of the Load cycle for passengers. Figure 9

1 is an illustration of the left side loaded and ready for operation of the vehicle and the right side at the start of the
2 loading operation, emphasizing the independence of the two sides of the Gravity slide drive mechanism.

3 Figure 10 A and B are an illustration of Isometric views of the present invention on one
4 side of the vehicle for clarity. Figure 10 C is an illustration of a Plan view of the present invention for one side
5 of the vehicle.

6 Figures 10 A1, 10B1 are isometric views of an alternative embodiment with a vertical
7 extension/"safety cage" to protect passengers further. Figure 10 C1 is a plan view of the same arrangement.

8
9 Figure 11. is an illustration of the position of the "Safety Zones" that are targeted for
10 protection with the Protector shields.

11
12 Figure 12. A is an illustration of an isometric view of the Seat arrangement. Figures 12B
13 and 12C is an illustration of the Plan and Side Elevation of the seat arrangement. Figure 12 A1 illustrates an
14 alternative embodiment of the seat arrangement. Figures 12B1 and 12C1 illustrate the plan and elevation of this
15 embodiment. Figure 12 D1 illustrates an embodiment of the child seat. Figure 12 E1 illustrates an embodiment
16 with a different external profile for the seat providing greater protection to the passenger. Figures 12 F2 and 12
17 G2 illustrate isometric views of an embodiment of the safety harness and 12 H2, 12 I 2, 12 J 2 illustrate an
18 isometric view of another embodiment of the safety harness, in the normal state, with front impact anatomical
19 passive micro air bag deployed, and the head and neck anatomical micro airbags deployed respectively.

20 Figure 13. is an illustration of a drawing of isometric view of the present invention.

21 Figure 14 illustrates a horizontal cross section of an embodiment of the present invention
22 at the level of the upper primary slides.

23 Figure 15 illustrates a side impact with internal and external airbags deployed and the
24 passengers ejected away from the impact.

25 Figure 15B illustrates the deployment of the anatomical passive micro airbags in a front
26 impact and the passenger impact protection with the harness and shield. The left side passenger illustrates the
27 normal position for reference.

28 Figure 15 C illustrates a detailed view of the safety harness and its components.

29 Figure 16A illustrates a passenger ready to leave the vehicle. The safety harness/shield is
30 still in place.

31 Figure 16B shows the passenger in Figure 16 A after releasing the safety harness/shield
32 from the locks.

33 Figure 16C shows the same passenger in 16 A,B but with the safety harness/shield now
34 well above the head so that the passengers leave the vehicle by simply standing up.

35 Figure 16D shows the safety harness/shield unlocked from its mounts within the vehicle,
36 illustrating the flexibility to move within the vehicle under these conditions but not having the visibility to drive,
37 thereby ensuring that the safety harness/shield is used under driving conditions.

38 Figures 17 A,B show a schematic diagram of the passive air cushionsystem disclosed in
39 this invention.

Figures 18 A-J shows different views of the wheel chair arrangements deployed as passenger support mechanisms.

Figures 19 A-E show an embodiment of the customizable contoured multi – element seat.

Figures 20 A-C show an embodiment of the indo skeletal structure that includes special arrangements for front impact protection and other features for passenger convenience and comfort.

Figures 21 A-F show other alternative embodiments for front impact protection.

LIST OF REFERENCE NUMBERS

- 101 - Central Member of Indo-skeletal structure
- 102 - Lower Primary Slide
- 102' - Safety Beam Elements (may be a part of 2)
- 103 - Side impact shock absorbers
- 104 – External Air Bags
- 105 – Perforation Shields
- 106 – Protector Shields
- 107 – Upper Primary Slide
- 107' – Slide Beam (may be a part of 7)
- 108 – Auxiliary Beam.(fixed or sliding)
- 109 – Multi-element contoured passenger seat
- 110 – Vehicle Shell/Body
- 111 – Secondary Slides/Impact decouplers
- 112 – Locking devices
- 112A-Pivot for Protector shield
- 113 – Proactive Velocity/Distance Detectors
- 114 – Internal side impact airbag
- 115 – Spring device for manual slide
- 116 – Inside door open button
- 117 – outside door open button
- 118 – Beam pivot for Gravity slide drive ejector
- 119 - Safety Harness
- 120 – Support for Safety Harness
- 121 – Bottom of seating surface of the contoured seat
- 122 – Contoured arm rests
- 123 – Child seat attachment
- 124 – Impacting body
- 125 - Vertical extensions/ Safety Cage (fixed or sliding)
- 126 – Center console
- 127 – Secondary slide/Center console locks
- 128 – Instrumentation

129 – Center airbags-energy absorption/ passive head and neck anatomical airbag system
130 – Safety Harness Shield
131 – Safety Harness -Anatomical passive micro air bag and visco-elastic buffer
132 – Safety Harness elbow
133 – Safety Harness extending upper arm
134 – Safety Harness Pivoting lower arm
135 – Safety Harness Head and neck anatomical micro airbags (active or passive)
136 – Safety Harness Adjustable Head restraint
137 – Safety Harness Hinged support
138 – Safety Harness Locking Support
139 – Safety Harness passive micro airbag air reservoir
140 - Adjustable Hinge support on seat
141 – Foot rest
142 – Sacrificial chamber
143 – Micro air-cushion – displacement function
144 – Micro air cushion – support function
145 – Valves – air flow/fluid flow
146 – protected entity
147 – Fluid paths
148 – Wheel Chair Conversion - Seat lower cushion and support structure
149 – Wheel Chair Conversion – Chair Clamps
150 – Wheel Chair Conversion – Chair Cross support
151 – Wheel Chair Conversion – Primary Pivot with locks for Rear Wheel retraction
152 – Wheel Chair Conversion – Principal Rear Wheel Support
153 – Wheel Chair Conversion – Rear Wheel Support strut
154 – Wheel Chair Conversion – Secondary Pivot for Rear Wheel retraction
155 – Wheel Chair Conversion – Spring loaded locking support Sleeve
156 – Wheel Chair Conversion – Seat back
157 – Wheel Chair Conversion – Primary Pivot with locks for front wheel
158 – Wheel Chair Conversion – Wheel chair back pivot release
159 – shadow vertibra – air cell retainer
160 - shadow vertibra – lateral tilt return spring
161 - shadow vertibra –upper fixed slot fo lateral tilt return spring
162 - shadow vertibra –support flange
163 - shadow vertibra –upper slot for support flange
164 - shadow vertibra – left body
165 - shadow vertibra – right body
166 - shadow vertibra – left upper air cell socket
167 - shadow vertibra – right upper air cell socket

168 - shadow vertibra – lateral tilt air cell visco elastic damper tube
 169 - shadow vertibra – lateral support arm connector
 170 - shadow vertibra – - back support adjustable air cushions
 171 - shadow vertibra – left lower air cell socket
 172 - shadow vertibra – right lower air cell socket
 173 shadow vertibra – lower slot of r support flange
 174 – lower sliding slot for lateral tilt return spring
 175 - shadow rib – body
 176 - shadow rib – adjustable air cushions
 177 - shadow rib – tilt control connectors
 178 – shoulder bolster
 179 – Shoulder bolster adjustable air cushions
 180 - back support adjustable air cushions
 181 – Neck lateral support with deploying passive micro air bag
 182 – Head lateral support arms with deploying passive micro air bag
 183 – Head rear support adjustable air cushions
 184 – Neck rear support adjustable air cushions
 185 - Lumbar support adjustable air cushions
 186 – Adjustable Hip bolster
 187 – Adjustable Pelvic support
 188 – Axial contraction system – Central body tube
 189 – Axial contraction system - Body extender tube
 190 - Axial contraction system – front end connector tube
 191 - Axial contraction system – back end connector tube
 192 - Axial contraction system – front end
 193 - Axial contraction system – back end
 194 - Axial contraction system - front module
 195 - Axial contraction system – rear module
 196 - Axial contraction system – front module crank
 197 - Axial contraction system – rear module crank
 198 – passenger support plattform

DETAILED DESCRIPTION OF INVENTION

The present invention provides a passenger vehicle a structure that synergistically incorporates two functions. First, during lateral or side impacts, a means to decouple from impact, and protect passengers while projecting the remaining mass of the vehicle to decelerate the impacting body, and second, utility to passengers and drivers, in mounting and dismounting the vehicle with the comfort of contoured surround seats. The arrangement may in some embodiments use an indo-skeletal beam that allows such

embodiments to rely on compressive force transmission to transfer impact energy to the mass of the vehicle rather than shear loads that are required in the shell paradigm of construction in most current passenger vehicles.

The present invention may use Primary and Secondary slides on each side of the vehicle, to meet these objectives. The Primary slide has among other attached devices, a protector shield that bears the impact force in lateral or side impacts. Such protector shields may be hinged out for access if the sliding arrangement is not used. The Primary Slide may engage a central indo-skeletal beam in some embodiments. The Secondary slide is attached among other devices to possibly contoured surround seats. This slide may be activated under impact to guide passengers in their seats away from the impact zone.

The present invention may utilize a Safety Beam in the vicinity of the seats. However, there is an important advance over the Background art in that the Beam does not lock the passengers on the path of the energy transfer, but rather, conducts the energy of impact away from the passenger to the indo-skeletal frame or to the body members of the shell (collectively elements of the fixed body members) and thereby to the mass of the vehicle allowing independent motion of the passengers away from the impact.

The present invention may use proactively fired external airbags which for the first time provide a means to create a “Just in Time” deceleration zone on the side of a vehicle prior to impact but not deployed under normal operating conditions of the vehicle. Notably, Background art for external airbags that are either extended under normal operating conditions of the vehicle or require reactive deployment cannot function effectively, as the former will impede the maneuverability of the vehicle and the latter will not be able to create a deceleration zone in time for the impact.

Overall this invention provides a “bottom up” paradigm for the design of vehicles starting with the human environment and building outwards to the vehicle – in stark contrast to the conventional approach of design that starts with the vehicle and inserts within these constraints, the passenger environment. Moreover, this invention embodies a two level safety system. The first or the primary level is passive and has a negligible probability of failure. The second level is active and predictive or proactive, utilizing advanced technologies. However, complex advanced technology systems have the drawback of higher probabilities of failure. Therefore while the second level can reduce the level of injury in serious crashes, there is a non trivial probability of failure of this secondary system. Therefore it is necessary to build a primary system that is good enough in most cases to reduce injury levels in severe crashes. The paper in the Appendix includes simulation results for an embodiment of the primary system alone with a failure of the secondary system.

The following descriptions are for embodiments of the present invention. Deviations from this description in an embodiment is possible without deviating from the present invention.

PREFERRED EMBODIMENT

The following is a detailed description of some of the components of this embodiment. The seating arrangement of a passenger vehicle is shown in Figure 1. The cross section of the central member of the indo-skeletal structure (101) is fixed to the safety beam (102') and the lower primary slide (102). The Protector Shields (106) is firmly attached to the Upper Primary slide (107), which slides on the lower Primary slide (102). (The terms upper and lower being used for the slides to distinguish them and not representing a relative elevation of the slides). The construction of such protector shields would follow that of any impact

resisting body panel member of a vehicle, with the usual weight strength tradeoffs. Such construction is well disclosed in the background art. The sliding arrangement may use single element or multiple element direct contact low friction surfaces sliding on one another, roller bearings, ball bearing structures – all of which are well disclosed in the background art. The Protector Shield(106) are designed to cover the required “safety zone” as noted on Figure 11. The Upper Primary Slide (107) locks into the Central member of the indo-skeletal structure (101) in the operating position with locking devices (112). Such locking devices do not take any additional loads on impact, and may as a result follow the extensive background art for locking devices for example similar mechanisms to those used in automobile door locks. These locks may be activated by the ignition key switch for additional safety while the vehicle is operational. The Protector Shield (106) has attached on the outside a shock absorber (103), which may include external airbags (104). The construction of such shock absorbers follow the background art. Such external airbag (104) are protected from sharp objects on impact by a Perforation Shield (105). These perforation shields protect the external airbag (and the passenger) from sharp objects. The construction of such perforation resisting shields are well disclosed in the background art. Such Perforation shields may be attached by conventional means to the outer surface of the airbag and retained in the normal operating position using techniques used for airbags both internal and external disclosed in the background art. The Air Bag (104) is deployed with distance and velocity sensors (113) mounted on the Perforation shields (105). Distance and velocity sensors are used in other applications and their construction is well disclosed in the background art. The Upper Primary Slide (107), supports the secondary slide/Impact decouplers (111). In this embodiment this is firmly attached to the Upper Primary Slide until the impact when it is decoupled to slide away from the impact. The Secondary slide arrangement may use a friction based approach, or other approach, all of which are well disclosed in the background art. This embodiment has contoured surround Passenger Seats (109) that are mounted on the Secondary slides (111). These seats have internal Airbags (114) that deploy on impact and may “unfur!” upwards to protect the head or upper body as well. The construction of seat adjustment mechanisms are well disclosed in the background art. This Figure shows the impacting object on the left approaching the vehicle, but too distant to trigger any action.

In Figure 2, the impacting object has moved to a position that can now trigger the distance and velocity sensors (113). These sensors trigger the deployment of the External Airbags (104), and the shock absorbers (103). The internal airbags (114) may be triggered by conventional means disclosed in the prior art, explicitly or implicitly reacting to proactive or reactive impact detection. The internal air bags are designed to move the passengers and the passenger seats to the extent necessary through a Motion Space to a Safe Position on primary impact detection, and thereafter protect the protected entity – the passenger and the seat. Thereafter as illustrated in Figure 3, the External Airbags (104) and shock absorbers (103) deploy to provide the required deceleration zone for the impact. As a result on impact the energy of impact is partially absorbed by the External Air bag (104) and the Shock Absorber (103) and the remaining energy transferred to the massive components of the vehicle through the Protector Shield (106), the Upper and Lower Primary Slide/ Safety Beam (107, 102, 102’) to the Central element of the Indo-skeletal frame (101) and the body of the vehicle. Notably, the Secondary slides (111) decouple and slide the passenger seats (109) with the passengers away outside the path of the impact forces and protected by the internal Airbag (114). The Upper Primary Slide (107) on the side of the vehicle away from the impact is free to slide out with all devices mounted on it to provide a path for the

secondary slide (111) and the seats (109). In this situation it may be seen that the Upper Primary slide works as an impact-resisting beam on the side of the impact and a release and support mechanism on the side away from the impact. Figure 15 A illustrates the side impact with the deployed internal and external airbags, and the displaced passengers away from the impact in the vehicle sustaining the lateral impact. Figure 15 B illustrates the frontal impact support for the passenger on the right hand side. The Left hand passenger is shown in the normal position for comparison.

Figure 14 illustrates a horizontal cross section of the embodiment at the height of the upper primary slides (107). The central member of the indo-skeletal structure (101) is flanked by the upper primary slides (107) abutting the central member, with the protector shields (106) and the shock absorbers that include the external airbags (103,104) at the outer end of the upper primary slides. The perforation shields are shown at the outer extreme of the shock absorbers and airbags. In this embodiment there are two sets of upper primary slides on each side of the vehicle that can support two rows of seats (front and rear) one on each side with its own protection with the protection shields and shock absorbing devices.

An auxiliary slide beam structure (108) (as illustrated in figures 10A, 10B and 10C) may be attached to the central member of the Indo-skeletal beam (101) and locked into the protector shield when the vehicle is ready for operation, or be attached to the protector shield and slide out with the Upper Primary Slide (7), and get locked to the central member of the Indo-skeletal structure (1) in the operating position

Means for access for passengers in this embodiment as illustrated in Figures 5, 6, 10A, 10B and 10C. The seat (109) and secondary slide (111), slide out on the upper Primary Slide (107) to a position that lets the seat (109) protrude from the vehicle such that the passenger may simply stand in front of the seat and sit down on the seat (109). Thereafter the seat (109) is retracted on the Primary slide to the position as depicted in Figure 6, where the Upper Primary slide (107) is locked with the locking devices (112) in position for operation of the vehicle. The slide drive mechanism may be powered using approaches well disclosed in the background art such as servos, and pneumatic or hydraulic systems. The vehicle while in operation should have the Upper Primary Slide (107) retracted and locked. The ignition lock is used in this embodiment to ensure this practice.

While extended, the clearance on the side of the vehicle for the Easy Ejector will usually be in the range of about 20 inches to 30 inches. This could be substantially less than the clearance required for opening a conventional car door. This is particularly useful for parking in areas with limited clearance.

Figures 12A, 12B and 12C illustrates the detail of the seat (109). The seat (109) may be constructed with customizable multi-elements that conform to the desired shape and provide the desired support for the passenger. Such adjustments may be effected using conventional seat control devices. In this figure the Safety Harness (119) is secured to the sides of the contoured seat (109) between the arm rests (122). The safety harness (119) may be designed to protect the passenger in head-on collisions by providing a soft barrier in close proximity to the body but not necessarily touching the body. This arrangement may be preferred to seat belts that do not provide the extended surface area that the harness (119) provides and as result provides greater impact resistance for the same level of limiting forces that the body can withstand. Moreover, this arrangement

1 may obviate the need for a front collision airbag as the harness (119) may be high enough to support the face
 2 and neck under collision conditions. The harness may be constructed of pliable but semi-rigid material (such as
 3 high strength nylon) to provide support in a head on collision. A natural benefit of the arrangement of the
 4 harness (119) and its supports (120) is that lateral forces on the seat are also braced by the harness support (120)
 5 in the operating position. Figures 12 F 2 and 12 G2 illustrate an embodiment of the harness. Moreover the seat
 6 (109) may be constructed with reinforcing on the sides to further protect the passenger from crush injuries. The
 7 Seating surface (121) is illustrated in the same figure as are the arm rests (122). In conventional vehicle seat
 8 designs the door surface provides the only support on the external side surface which are usually limited to arm
 9 rests. This seat (109) provides surround support for the passenger particularly desirable on winding roads. The
 10 "Custom contoured seats" customized for each passenger may be created with a multi-element adjustable
 11 structure (manually with inserts or with computer controlled elements) that provide ergonomic passenger
 12 comfort providing where desired, lateral support in addition to the support that conventional seats provide, to
 13 cradle the entire lower body in the ejector seat. Similarly child seats (123) as in Figure 12D1, may be designed
 14 to protect children. Such seats can be inserted into the seat (109). The Safety harness may also have an
 15 attachment for providing greater support for infants and small children.

17 ADDITIONAL EMBODIMENTS

18 While the above embodiment uses a power slide drive, this embodiment differs in that a
 19 gravity slide drive is employed to move the slides for mounting the vehicle. Figures 7,8 and 9 describe this
 20 arrangement. This embodiment differs in the preferred embodiment above in that the Lower Primary
 21 slide/safety Beam (102, 102') are pivoted at the Central member of the indo-skeletal structure with pivots (118).
 22 As shown in Figure 7, this allows the lower slide to fall to a lower of two positions, that inclines the upper
 23 surface of the Lower Primary slide (102) adequately to allow the upper Primary slide (107) to slide outwards to
 24 the loading position assisted by the weight of a passenger in the seat and the additional assistance of the Spring
 25 arrangement (115). The passenger may dismount from the vehicle when the slide is fully extended as shown in
 26 Figure 7. Each side of the vehicle has independent slides and may be operated by passengers independently.

27 When the passenger dismounts from the seat the Upper Primary slide (107) in its
 28 extended position moves to the higher of two positions about the Pivot (118) as illustrated in Figure 8. This
 29 move inclines the Upper surface of the Lower Primary slide adequately to allow the weight of a passenger to
 30 work against the spring arrangement (115) and move the slide to the operating position. This move up of the
 31 Lower Primary Slide (107) may be effected by mechanisms well disclosed in the background art. The Slide as
 32 depicted in Figure 8, is now ready for a new Passengers to mount. When the passenger sits on the seat (109), the
 33 weight of the passenger works against the spring mechanism (115) to move the slide to the operating position as
 34 depicted on the left hand side of the figure 9 and lock the slide in the operating position. The Upper Primary
 35 Slide may be unlocked by the passenger by depressing the Inside Door Open Button (116). Activating this
 36 button in addition allows the lower primary slide (102) to move and be locked to the loading inclination - the
 37 lower of two positions, and the Upper Primary Slide (107) is free to slide out with the passenger. At this point
 38 the arrangement has completed a full cycle and is in the position depicted in Figure 7.

The above cycle represents operation of the Gravity Slide Drive when there is a passenger in the seat (109) when the Slide moves to and from the operating position as on the left of Figure 9. When a passenger dismounts however, and the Slide arrangement needs to be retracted without a passenger in the seat, the weight of the passenger is no longer available for aiding the motion of the slide to the operating position, and the slide must be pushed in against the action of the Spring Arrangement (115) and locked in place at the operating position. When a new Passenger wishes to mount the vehicle, he/she will press the Outside Door Open Button (117) which releases the catch that holds the Upper Primary Slide beam in place but does not affect the movement of the Lower Primary Slide (102) about its pivot (118). The seat as a result slides out on the Upper Primary Slide assisted by the Spring arrangement (115) to the position for mounting the vehicle as depicted in Figure 7. The spring arrangement (115) is designed to be such that it provides a force just adequate to move the Upper Primary Slide out with no passenger in the seat.

Some alternative embodiments may have multiple positions for the inclinations of the safety beams from the center of the vehicle, in the loading position to accommodate the varying road inclinations that may make a single inclination of the safety beam in the loading position inadequate. In such an embodiment the operator will have the facility to switch to the best loading inclination dependant on the inclination of the road. This will overcome some of the disadvantages of regular car doors on steep hills. Moreover, this arrangement can also function as a shock absorbing device for the comfort of the passengers in vehicles under operating conditions. A possible embodiment to achieve this can have a range of angular inclinations for the operating position, the range being set so that the transfer of the compressive load on impact through to the fixed body members of the vehicle or the central beam is achieved. The Safety beams are spring or shock absorber mounted in a vertical plane relative to the central beam and the fixed body members of the vehicle. When a bump in the road is encountered the safety beams pivot on the center and swing higher at the center thereby isolating the passenger from the road.

Some embodiments of the multi-element contoured seats may have a structure that provides anatomically accurate support for the body as illustrated in Figures 19 A,B,C,D and E. This seat architecture may be used in a wide variety of applications outside vehicles as well. Conventional car seats are a set of two or possibly three rigid structures - the seat bottom, the back and the head rest. These have some mobility for comfort. However there are two factors that militate against their comfort and the level of protective support they can provide in collision situations. First, one size must fit all passengers and drivers. The mobility provided for the seat bottom, seat back and head rest provide limited flexibility for passengers of different sizes. Second, there is little lateral support for the body that could be vital in a side collision, and third, in a vehicle in motion on a rough surface, the shock absorption provided to all parts of the upper body is the same. - the seat back is rigid once set up by the passenger - this stands in contrast with the internal shock absorption of the human body, where the spine provides differential shock absorption to different parts of the body, increasing the shock absorption towards the head. This last factor implies that conventional seat backs cannot remove vibrations from both the top and the bottom of the upper body as the body's own shock absorption system will move differentially to the seat back along the length of the spine. The embodiments of this invention illustrated in figures 19, improve these characteristics of seats.

Figures 19 A and B show two view of a shadow vertebra of the seat. The design of this vertebra is to provide auxiliary support for the body. The structure shown is one of several possible structures for embodiments of this invention. The body of the vertebra in this embodiment is split into a left body (164) and a right body (165) these elements are permanently bonded or fixed together by bolts. The body has two cavities on each of the top and the bottom surface – the air cell sockets. These hold two air cells on the left and the right side. These air cells are supported on the sides by the air cell retainers (159) that slide in and out of the air cell sockets (166, 167, 171, 172). The air cells them selves are made of a pliable and inflatable material, or alternatively a material that can fold within the cell supports. Each pair of air cells are separately inflatable by a multi channel air pump that is installed in the seat embodiment. There is a connecting tube between the left and the right air cells housed in the lateral tilt air cell visco-eleastic damper tube. This tube allows limited air flow between the left and the right chambers to permit lateral tilting of the vertebrae relative to each other. This motion hover is corrected by the lateral tilt return spring (160) that ensures that in the normal position the vertebrae are aligned vertically. This lateral tilt return spring is fixed on one end to a vertebra in the upper fixed slot for lateral tilt return spring (161) and can slide within the next vertebra in the lower sliding slot for lateral tilt return spring (174). Orthogonal support is provided between the vertebrae with the support flange (162) that is fixed at one end in the lower slot for the support flange (173) and is slidably mounted in the adjoining vertebra's upper slot for support flange (163). The flange is sized to allow limited lateral tilting as the vertebra tilts laterally, but provides firm back support. Notably the upper and lower slots for the support flange may be inclined slightly so as to take the form of the human spine. The body contact is made on the back with the back support adjustable air cushions (170), which in most embodiments are contoured to the shape of the bode and is illustrated as an ellipsoid for clarity. These air cushions are inflatable and the pressure may be adjusted to the comfort of the passenger. There may be a spring loaded cable that is threaded through the vertebrae to tie them together. The spring loading will work against the air cell pressure as the gets elongated with higher air cell pressure. Ideally there can be as many of the shadow vertebrae as vertebrae in the human body although some embodiments may choose some economy in the number of such shadow vertebrae. Figure 19C illustrates two adjoining shadow vertebrae. One of these are for supporting the thorax region and therefore have attached the shadow rib body (175) and the related shadow rib adjustable air cushions (176) (shown as ellipsoids for clarity but in most embodiments will be contoured to take the shape of the body. These air cushions are inflatable for passenger comfort. The air supply being led to the cushions along the rib body and down the shadow spine to the multiple channel control air pump which also supplies air pressure of each of the many air cushions and air cells in the seat embodiment. The shadow ribs are supported by the tilt control connectors (177) that may adjust the angle of the shadow ribs. Figures 19 D and E. illustrate one possible version of this embodiment. Here the shadow vertebrae are stacked up to provide support for the head the neck the shoulders, the thorax and the lumbar region. The head rear support adjustable air cushions (183) provide forward support for the head while the Head lateral support arms with deploying passive air bag (182) provides lateral support particularly during side collisions with deploying passive micro airbags. Similarly the neck has rear support from neck rear support adjustable air cushions (184) and lateral support from Neck lateral support with deploying passive micro air bag (181). The shoulders are supported by the shoulder bolster (178) and the shoulder bolster adjustable cushions (179). The shoulder bolster being pivotally attached to a vertebra of the shadow spine and allowed

1 limited pivotal motion vertically to allow the passenger to move his/her upper arms upwards at normal speed.
 2 However, the shoulder bolster will resist rapid motion of the upper arms and shoulders as in a collision thereby
 3 supporting the passenger. This differential movement characteristics can be achieved by approaches well
 4 disclosed in the background including viscous loading of the coupling. Lumbar support is provided by the
 5 Lumbar support adjustable air cushions (185). The entire array of the shadow vertebrae may be elongated and
 6 contracted by changing the pressure in the air cells thereby providing the optimal sizing for all heights of
 7 passengers. The lateral support and back support cushions may be inflated to provide width control and support
 8 for passengers of different shapes. Adjustable hip bolsters provide lateral and forward support while the
 9 adjustable pelvic support (187) provides vertical support for the passenger. The illustrations exclude the leg and
 10 arm supports that are part of the embodiment for sake of clarity. Spring supports can substitute for the air cells
 11 in the vertebrae but will not have the advantage of viscous lateral resistance and independent height control.
 12 Overall height can however be controlled with the cable threaded through the vertebrae. Motion control of the
 13 seat elements can be achieved with devices well disclosed in the background art including servos, and
 14 pneumatic and hydraulic systems.

15 Considering the complexity of the seat systems including the multi channel inflators for
 16 each of the air cells and the air cushions along with the mechanical controls for inclining the shadow ribs and
 17 the pelvic and hip supports, it would normally be necessary to use a closed loop feedback with computer
 18 control. Pressure sensing of each air filled device will provide feedback on the resistant force of the human body
 19 and therefore firmness of the support. This information can be used to provide the firmness control desired by
 20 the passenger. One computer controlled scheme could be where the passenger inputs gender weight, and height
 21 and the computer alters the size of the seat by inflating and deflating air cells and cushions accordingly and the
 22 provides several alternative configurations that the customer can select. The customer can then customize
 23 firmness and variations on the seat presets.

24 Finally the shoulder bolsters and shadow ribs may have deploying micro air cushions that
 25 hold the passenger in the event of a collision.

26 Yet another variation of this embodiment discharges the air in the adjustable air cushions
 27 when passengers leave the seats, and then reinflate these air cushions when the new passenger sits down with air
 28 that is preheated or precooled to the preferred temperature of the passenger. Thereafter the air cushions will
 29 provide insulation at that temperature for the seating surface.

30 Embodiments, particularly those that utilize the indo-skeletal structure may include the
 31 following additional embodiments and variations thereof for frontal and rear impact protection and passenger
 32 comfort and convenience. The additional structure is illustrated in figures 20 A,B and C. The passenger support
 33 platform (198) represents the set of machinery for that purpose. It will take the shape needed to support the
 34 variety of structures that are described in this invention. It is supported either in the middle or on the edges by
 35 the Central body tubes (188). The first tube that fits into the central body tube is the Body extender tube (189)
 36 This optional tube is slidably connected to the central body tube and may be moved in and out by servo motors
 37 or pneumatic/hydraulic pistons and cylinders. However the inner tube is axially supported by a compression

1 resistant shock absorber which in turn is mounted rigidly with regard to the outer central body tube in all
2 poitions that the body extender tube can take. The Body extender tube has functions that include extending the
3 wheel base of the vehicle under computer control particularly in drive by wire vehicles, thereby improving the
4 comfort of the vehicle and second increasing the wheel base contingent on vehicle speed such that in the event
5 of a collision there is a longer deceleration space. The shock absorber will become longer and and shorter to
6 accomodate this need and can for example be air shock absorbers. The correlation of speed and length will
7 normally be computer controlled to provide statistically appropriate deceleration distances for the speed of the
8 vehicle at any time. Notably the steering arrangements and other vehicle systems may also need to be
9 compensated to accommodate the change in wheel base to ensure driver convenience and precise control of the
10 vehicle. The Front end connector tube (190) has a shock absorber in series with a servo or pneumatic/hydraulic
11 controlled actuator for axial movement in and out of the body extender tube (189) as does the back end
12 connector tube ((191). 190 and 191 are connected to the front and back ends respectively which include the
13 front and back wheels.and bumper arrangements. The front module – which may be the engine or hybrid unit is
14 pivoted on brackets at the front end of the front end connector tube, thereby allowing the module to rotate
15 upwards about this pivot. Notably the module will be signifvcantly massive and will require strong supports
16 and pivots. The front module crank is pivotally attached to the body extender tube and also pivotally attached to
17 the front module as shown in figure 20 A. Therefore if there is a movement of the front end towards the body
18 extender tube the front module crank would swing the front module about its pivot in the front towards the
19 vertical direction.

20 There are at least two functions for this motion. First in the event of a front collision the
21 force will compress the shock absorbers on the end of the front end connector tube and thereby force the crank
22 to pivot up the front module. This angular acceleration of the massive front module will absorb energy of the
23 impact and acting as a “fly wheel”, remove acceleration spikes that the passenger would otherwise sustain and
24 in addition due to its vertical acceleration increase the traction on the front wheels thereby increasing the
25 braking friction resistance that can be offered. Finally in the event of a collision the inclining front module will
26 divert the impacting vehicle over the passenger space. This action is illustrated in figure 20 C. Second,
27 particulary for drive by wire vehicles, the front and back end connector tubes may be retracted by servo or
28 pneumatic/hydraulic rrangements, to pivot up the front and back modules thereby reducing the vehicle length
29 substantially and providing better curb visibility to the driver particularly while paaking. This is illustrated in
30 Figure 20 B. Notably the wheels are maintained in the same orientation to the road surface and may be steered
31 as desired with the same mechanisms. For conventional vehicle architectures the pivot of the front module and
32 engine with the front end connector tube should be near the wheel axis to facilitate this additional feature.

33 The same value is derived in the rear structure as the front structure for rear collisions and
34 in front collisions and in parking. The arguments are similar.

35
36 Another embodiment may have a single but broad set of central body tube body extender
37 tube and the back/front end connector tubes with a split front or back module and connection of the front / back
38 connector tube with the front /back ends respectively in the middle. Yet another configuration may have a single

1 central body tube and body extender tube but then have a “T” shaped structure on the back or the front to have
2 separate left and right front and/or back end connector tubes connected with the front end at either side. In the
3 event the body extender tube is not used the connection of the front/back module cranks will be to the central
4 body tubes.

5 For embodiments that use an exoskeletal or shell design, an additional embodiment
6 deploys airbags in the space surrounding the engine components to change the characteristics of the crumple
7 zone. Moreover in addition some of these embodiments have the passenger cabin slidably and detachably
8 connected to the rest of the vehicle and mounted behind these deploying airbags such that on impact, the cabin
9 detaches from the vehicle and slides backwards in a controlled fashion to ensure the integrity of the cabin.

11 ALTERNATIVE EMBODIMENTS

12 In an alternative embodiment to the preferred embodiment, the present invention may use
13 hinged Protector Shields (106) that lock into the Primary Slide (107) when closed. This will allow the
14 arrangement to work for mounting and dismounting the vehicle with either the Primary Slides deactivated or
15 non-operational as well as when they are functional. The seats may also be mounted on rotating mechanisms
16 or extension arms rather than a primary slide, to assist passengers in mounting and dismounting.

17
18 Another alternative embodiment utilizes co-axial sliding mechanisms that constitute said
19 rotating mechanisms rather than the primary slides such that the fixed and rotating members of said rotating
20 mechanisms have an adequate area of contact and reaction to support lateral collision forces.

21
22 Another alternative embodiment is illustrated in Figures 5A and 6A. The “door” that
23 contains the perforation shield (105) with distance/velocity sensors (113), the external airbags (104), the shock
24 absorbers (103) and the protector shields (106), hinges down on the pivot (112A) to provide support for the
25 upper primary slide. The inner surface of the Protector shield is designed to perform the function of the lower
26 Primary slide (102). This embodiment will be particularly useful for larger vehicles with a plurality of seats on
27 each side of the vehicle. These multiple seats may be mounted on separate sections of upper primary and
28 secondary slides.

29 Another alternative embodiment is illustrated in figures 1D to 4D where the Shock
30 Absorbers (103) excluding the External Air bags (104) are mounted on the inner surface of the protector shields
31 (106). As may be seen from the drawings, in this particular embodiment, the shock absorber excluding the
32 external air bags are locked directly to the lower primary slide (102, 102') in the operating position, although in
33 another configuration the locks may be between the protector shield and the lower primary slide in the operating
34 position. Such embodiments may be designed to allow limited intrusion of the protector shield with resistance
35 provided by the shock absorber (103) thereby reducing the peak acceleration sustained by the vehicle body
36 under impact. Notably, as the passenger environment is protected and moves away from the impact, crush
37 injury to the passenger is avoided. This is a unique feature of this invention where both the crush injury of the
38 passenger and the peak acceleration of the vehicle (and the passenger as a result) may be minimized at the same
39 time. Conventional designs try to minimize intrusion by bracing the side of the vehicle with beams and thereby

1 increasing the peak acceleration of the vehicle, or increasing intrusion to reduce the peak acceleration but
2 allowing greater crush injury.

3 Another alternative embodiment may have a contoured safety harness with a different
4 shape to that of the preferred embodiment. Figures 12 A 1 to 12 C1 illustrate an embodiment of a safety harness
5 using a slightly different geometry but performing the same function in the same way as in the preferred
6 embodiment.

7 Some embodiments of the multi-element contoured seat may have sides that fold down and
8 away from the passenger. This feature is useful for the inner side of the passengers near the side of the vehicle
9 and for both sides of the passengers in the middle of the vehicle, if the center seats are fixed and not ejectable.
10 Notably however, the sides lock in the operating position and brace the seat from lateral compression, thereby
11 protecting the passenger.

12 Some embodiments of the seats may have sides that could include arm rests, side bolsters
13 and other elements as disclosed in this invention, that that drop down or back on the door or access side at the
14 time of egress and ingress, particularly in embodiments that use conventional doors for access. Activation for
15 these movements can be with the switching on and off of the ignition switch for the vehicle.

16
17 Yet another embodiment raises the seat bottom at the time of egress and ingress with
18 servos or pneumatic/hydraulic systems, so that the seat members on the sides of the seat are relatively lower to
19 the seat bottom thereby facilitating egress and ingress of the passenger. Moreover, arrangements to raise the
20 seat bottom may in addition in some embodiments help negotiate a high "door" sill by the sliding or rotating
21 seats at egress and ingress.

22 Yet another embodiment using conventional doors, has the arm rests on the door side
23 integrated in to the doors but protected and decoupled from the door members on its outside by inside air bags.
24 This design would have these arm rests locking into the seat when the door is closed thereby providing the
25 decoupling for the entire seat with the inside airbag during lateral impact.

26 Another alternative embodiment uses shock absorbing devices mounted at each end on
27 each of the two surfaces of the impact decoupler/secondary slide substituting or supplementing the inside
28 airbags.

29 Another alternative embodiment may have an auxiliary slide behind the seat and of any
30 convenient height. This embodiment is shown in figures 1C -4 C. The figures illustrate the working of the
31 current invention with a high section of the central member of the indo skeletal structure behind the seats, but
32 abutting the auxiliary beams in the operating position. As the High section of the central member (101) is
33 behind the seats and the secondary slides (111), the seats and the secondary slides are free to move across the
34 vehicle under impact as shown in figure 4 C.

35 Yet another alternative embodiment has an external seat profile as illustrated in figure 12
36 E 1. The higher rectangular external profile provides greater protection to the passenger.

37 Yet another alternative embodiment has a vertical extension/ "safety cage" (125) as
38 shown in figure 10 A1, 10B1 and 10C1. Here the vertical extension/safety cage engages a beam across the top
39 of the vehicle that may be supported by the shell structure of the vehicle (the figure shows only half the width of

1 the vehicle). Such a safety cage/vertical extension can provide protection in a roll over situation and also
2 provide additional compressive strength for the vehicle, and may function as a fixed or retractable roll bar. In
3 some embodiments such a vertical extension “safety cage” will perform the function of the “B” pillar of the
4 vehicle under lateral impact. Notably no “B” pillar is needed to support rear door hinges in the present
5 invention. Moreover, in some embodiments the beam arrangement across the top of the vehicle or other support
6 structures on the roof section of the shell may be designed to be rigid on compression but telescope out with the
7 secondary slides under impact using appropriate logic to drive the locking mechanisms, thereby providing a
8 protective cage even when the seat is in the ejected state.

9 Yet another embodiment, deters a roll over following side impact, by implementing an
10 “outrigger” arrangement having reinforced upper primary slides and/or secondary slides and bracing brackets
11 anchored to the fixed members of the vehicle that hold these slides in their extended substantially horizontal
12 position after extension under impact, without permitting them to buckle under a vertical forces encountered
13 under the initial stage of a roll over situation.

14 The preferred embodiment has the external airbags or shock absorbers triggered on
15 detection of an expected impact as noted. This implies that on the far side (non-impact side) if there is possible
16 secondary impact from a second object, the same mechanisms will deploy the external airbags on the second
17 side, thereby protecting the far side occupant in the event of a second object hitting the vehicle soon after the
18 first. An alternative embodiment can have distance/velocity sensors mounted in positions on the front and back
19 edge of the perforation shields or protector shields to facilitate better detection of objects approaching the
20 vehicle at wide angles to the perpendicular direction. Yet another alternative embodiment to this will have both
21 impact side and far side external airbags deploy on detection of the first impact.

22 Another alternative embodiment has a safety harness/shield as illustrated in Figure 12H2.
23 This embodiment of the safety harness is mounted on spring loaded hinged supports at the head support section
24 of the multi element adjustable seat (137) - similar to conventional supports for the headrest, and to lockable
25 supports between the arm rests (138) or on the side bolsters of the multi element adjustable seat. The spring
26 loading will support the weight of the harness and thereby retract the harness when unlocked. The harness
27 includes a hinged and spring mounted shield (130) that may pivot on the lower safety harness support (138),
28 The passenger side of the shield, has on its surface an implementation of a Passive Air Cushion System that
29 uses the pressure in one or more sacrificial chambers which under pressure transfer air to one or more micro-air
30 cushionsthat protect high priority anatomical regions. In this embodiment, the passive anatomical micro air
31 cushion (131), derives it inflation source from the sacrificial chamber (139) at the lower end of the shield of the
32 safety harness, that is compressed by a much greater body mass under impact. In a frontal collision the force of
33 the more massive parts of the body on the sacrificial chamber will deploy the passive anatomical micro-air
34 cushions to protect the face and the neck. The narrower sections of the aircushions and flow control
35 mechanisms if installed, will cause some visco-elastic behavior and in addition cause air speed amplification to
36 create faster deployment. While this mechanism activates the shield (130) may pivot down to take some of the
37 impact energy. The shield is shaped to the contour of the human body head and neck when it is forced forward
38 as in a frontal collision. This embodiment may in addition have multiple or variable position harness support
39 anchor points on the arm rests or the side bolsters that are part of the multi-element seat, to accommodate people

1 of different proportions. Moreover this embodiment may have in addition an additional bracket that moves the
2 anchor point of the lower safety harness locking supports substantially forward, and provides a supplementary
3 passive anatomical micro-air-cushion that can be mounted on the permanent micro-air-cushion on the shield, to
4 accommodate pregnant women, and the special critical force distribution they can withstand.

5 In this embodiment, the two pivoted arms swing forward under collision forces the
6 moment created by the shield with the body pressure against it, and extends the upper extending arms (133) to
7 absorb some of the shock and to provide a space for the forward movement of the upper body. The elbows
8 (132) facilitate the relative angular movement of the upper arms and lower arms of the safety harness (133,134).
9 They are spring loaded to ensure that they support the lower parts of the harness when unlocked to allow the
10 entire harness to move up and away from the body when unlocked without any force being applied. Under side
11 impact the passive anatomical head and neck micro-air-cushions deploy to protect the head and neck under
12 relative lateral acceleration. Notably the passive anatomical head and neck micro-air-cushions can be actively
13 deployed or as in this embodiment passively deployed by a discharge of air from sacrificial chambers between
14 the seats or on the outer surface of the seats and mounted on each of the seats, so that lateral pressure will inflate
15 the anatomical head and neck micro-air-cushions. The sacrificial chambers offer secondary impact protection
16 by cushioning the seat. Notably this embodiment does not use any active airbags in the vicinity of the human
17 body, reducing the risks associated with the high energy external deployment devices. The adjustable head rest
18 (136) follows conventional design but is here mounted on the safety harness hinged mounts.

19 Figure 12 I 2 shows the passive anatomical micro-air-cushions deployed (the sacrificial
20 chamber has been compressed and the top region is full and ready to protect the face and neck in a frontal
21 impact. Figure 12 J 2 shows the anatomical head and neck passive micro airbags deployed under side impact,
22 ready to support the head and neck in a side collision. Notably this embodiment uses a new concept where the
23 impact energy is redeployed for protecting vital parts of the impacted object which are often embedded inside
24 the object, using fluid transfer – in this case air transfer. Force and velocity amplification or deamplification can
25 be achieved with the geometry of the interconnections, the sacrificial chambers and the micro-air-cushions.
26 The sacrificial chambers can be used for secondary impact protection as well by carefully controlling the flow
27 parameters. This is illustrated in Figure 17. The approach obviates the need for active airbag technologies in the
28 vicinity of sensitive equipment, living organisms and indeed people.

29 This embodiment of the harness allows movement within the vehicle for passengers when
30 it is unlocked and allowed to swing up within the vehicle as shown in Figure 16D. However, visibility is
31 somewhat obstructed preventing the driver from driving without locking the harness in place.

32 In this embodiment of the safety harness entering and leaving the vehicle are facilitated by
33 the entire device swinging away from the body as shown in Figures 16 A,B and C. The passenger simply needs
34 to stand up to leave. To enter the passenger simply sit down and place his/her feet on the foot rest (141) and
35 retract the slider mechanism. This embodiment also has radar or infrared detectors as on elevator doors to detect
36 limbs in the way of the retracting sliding mechanism for the protection of the passengers.

37 Figure 15C shows the parts of this embodiment and the adjustable arm rests.

38 Another embodiment of the shield on the safety harness has a folding section at the top
39 that can be straightened and locked in place for adults and folded down for children.

Another embodiment uses flexible netting on part of the shield surface to protect passengers under impact. In this embodiment, the shield has a frame on which the netting is deployed. The upper end of the frame is adequately bent forward and then downwards to ensure that the passenger head and neck do not strike the frame under frontal collision. In yet another embodiment of this arrangement, the shield of flexible netting is designed for the head and neck and is normally retracted forward, and deployed on impact by initial forces by the lower torso of the passenger against the lower part of the safety harness/shield.

Yet another variation of this safety harness with netting on a frame, has telescoping frame members on the sides so that the height of the frame is adjustable by retraction of the telescoping members to accommodate children and small adults.

Yet another embodiment of the harness has an upper section of the safety harness consisting of spring mounted support arms mounted in the vicinity of the head rest and designed --when pulled down by the passenger --to swing down and over the passenger head and in front of the passenger. The support arms each having telescoping sections that connect to the shield, such telescoping sections having arrangements for an inertial ratcheting that prevent extension of these telescoping arms in the event of a sudden tension as in an impact. The lower section of the harness consists of short adjustable belts or arms that can be locked on the sides of the seat or on the inside of the arm rests as in a four point seat belt. This embodiment provides all the benefits of a four point seat belt but in addition has the benefit of head and neck support in the event of a collision. This arrangement allows protection with the telescoping sections and the adjustments on the lower end of the harness for different sized passengers.

Yet another embodiment utilizes the passive anatomical micro air cushion (131) at the top of the shield/harness that derives its inflation source from the sacrificial chamber (139) at the lower end of the safety shield/ harness. However, in this embodiment the anatomical micro air cushion is limited to only the top edge of the shield to support the head, neck and the upper thorax when deployed under collision conditions. This anatomical micro air cushion (131) is supported by pairs of telescoping tubes the lower member of each such tubes being fixed to the harness/shield support in the vicinity of the sacrificial chamber, and the upper member of each pair of telescoping tubes are attached to the passive anatomical micro air cushion (131). The outer tubes have contoured semi-rigid materials to conform broadly to the body shape. The lower and upper members of each pair telescope into one another co-axially, and are lockable in different longitudinal positions relative to the other member of the pair, thereby providing for a variable height anatomical micro air cushion. Airflow under deployment conditions is conducted either directly through said telescoping tubes or separator tubes that have an "accordian" collapsible structure that can extend as the telescoping tubes do, and may be placed inside said telescoping tubes. The length of the telescoping tubes may be manually set with the lock in other embodiments set by automated or computer controls that sense the size of the passenger from selected elements of the multi-element contoured seat.

Yet another embodiment has a harness as in figure 12H2 except that there is harness support arm only on the outer side of the passenger towards the side of the vehicle. (i.e. in these embodiments there is one Safety Harness elbow (132), one Safety Harness extending upper

Another embodiment uses flexible netting on part of the shield surface to protect passengers under impact. In this embodiment, the shield has a frame on which the netting is deployed. The upper end of the frame is adequately bent forward and then downwards to ensure that the passenger head and neck do not strike the frame under frontal collision. In yet another embodiment of this arrangement, the shield of flexible netting is designed for the head and neck and is normally retracted forward, and deployed on impact by initial forces by the lower torso of the passenger against the lower part of the safety harness/shield.

Yet another variation of this safety harness with netting on a frame, has telescoping frame members on the sides so that the height of the frame is adjustable by retraction of the telescoping members to accommodate children and small adults.

Yet another embodiment of the harness has an upper section of the safety harness consisting of spring mounted support arms mounted in the vicinity of the head rest and designed --when pulled down by the passenger --to swing down and over the passenger head and in front of the passenger. The support arms each having telescoping sections that connect to the shield, such telescoping sections having arrangements for an inertial ratcheting that prevent extension of these telescoping arms in the event of a sudden tension as in an impact. The lower section of the harness consists of short adjustable belts or arms that can be locked on the sides of the seat or on the inside of the arm rests as in a four point seat belt. This embodiment provides all the benefits of a four point seat belt but in addition has the benefit of head and neck support in the event of a collision. This arrangement allows protection with the telescoping sections and the adjustments on the lower end of the harness for different sized passengers.

Yet another embodiment utilizes the passive anatomical micro air cushion (131) at the top of the shield/harness that derives its inflation source from the sacrificial chamber (139) at the lower end of the safety shield/ harness. However, in this embodiment the anatomical micro air cushion is limited to only the top edge of the shield to support the head, neck and the upper thorax when deployed under collision conditions. This anatomical micro air cushion (131) is supported by pairs of telescoping tubes the lower member of each such tubes being fixed to the harness/shield support in the vicinity of the sacrificial chamber, and the upper member of each pair of telescoping tubes are attached to the passive anatomical micro air cushion (131). The outer tubes have contoured semi-rigid materials to conform broadly to the body shape. The lower and upper members of each pair telescope into one another co-axially, and are lockable in different longitudinal positions relative to the other member of the pair, thereby providing for a variable height anatomical micro air cushion. Airflow under deployment conditions is conducted either directly through said telescoping tubes or separate tubes that have an "accordian" collapsible structure that can extend as the telescoping tubes do, and may be placed inside said telescoping tubes. The length of the telescoping tubes may be manually set with the locks or in other embodiments set by automated or computer controls that sense the size of the passenger from selected elements of the multi-element contoured seat.

Yet another embodiment has a harness as in figure 12H2 except that there is a safety harness support arm only on the outer side of the passenger towards the side of the vehicle. (i.e in some of these embodiments there is one Safety Harness elbow (132), one Safety Harness extending upper arm (133)

1 and one Safety Harness Pivoting lower arm (134). Moreover the safety harness/shield support arm is designed
2 such that upon release from across the lap of the passenger, the shield flips to a vertical plane in the vicinity of
3 the vertical plane of said support arm. Thereby permitting the safety harness to swing over the head of the
4 passenger even when the seat is only partially displaced for entry or exit from the vehicle. Often this may be
5 useful when there is limited access space next to the vehicle.

6 Yet another embodiment, principally for vehicles with drive by wire technologies, has
7 the vehicle controls mounted on the shield. If a steering wheel is used this may be mounted on the front surface
8 of the shield (on the surface opposite the passenger). The steering wheel or other controls may have distance
9 adjustments for ergonomic positioning.

10 Yet another embodiment principally for drive by wire technologies, has the driver
11 controls mounted on the contoured arm rests of the car. Adjustments for the arm rests will include further
12 controls for the ergonomic positioning of these controls on the arm rests.

13 Vehicles, principally those that utilize drive by wire technologies with either of the above
14 configurations, will have the entire area below the windshield free of controls. This embodiment utilizes this
15 area for a GPS driven positioning display that mimics the view ahead of the driver. The display system may use
16 vector imaging techniques or non-linear image mapping techniques that are well disclosed in the background art
17 that provide the same perspective to the driver on the display as what he sees on the road ahead, thereby
18 minimizing mental processing of information in establishing a correspondence between the image and the actual
19 physical position and orientation of the vehicle thereby reducing reaction time for action by the driver.
20 Furthermore, the positioning of the display just below the screen ensures that there is minimal spatial
21 disorientation of the driver in turning his/her head to look at the screen thereby reducing further the mental
22 information processing needs and improving further the reaction time of the driver. In some embodiments
23 when there are controls such as a steering wheel in front of the driver, a fixed or a "pop up" screen just below
24 the windshield or a projection onto the lower windshield may be utilized. The image may include the
25 destination and path to that destination and may be at a different scale to the perspective of the driver ahead of
26 the vehicle. This embodiment and variations provide a unique system that conventional GPS navigation systems
27 do not provide in speeding up driver reaction times.

28
29 Another embodiment has air conditioning micro-ducts on the seating surfaces and the
30 safety harness/shields, for the comfort of passengers, particularly in open vehicles.

31
32 Another alternative embodiment has the "Open" switch for the slide on the inside of the
33 vehicle designed the "press bar" so that the intuitive reaction of the passenger to "open the door" is harnessed.
34 However, this can be deactivated when the vehicle is in motion.

35 Another alternative embodiment has a center console that is designed to crush under
36 impact as shown in Figures 1F – 4F, thereby minimizing the ejection of the far side passenger on impact.

37 Another alternative embodiment has the internal airbag partially filled at all times, so that
38 in the event of no deployment of the external airbags either because of technology failure or non installation or
39 other reason, the passenger and seat arrangement are cushioned even prior to further inflation of the internal

1 airbag on deployment on impact. Shock absorbers may supplement the operation of the internal airbags in this
2 embodiment with partially inflated internal airbags under normal operating conditions.

3 Another alternative embodiment can have the internal airbags deployed on impact as
4 noted with such deployment effected by inflation by some of the compressed air of the external airbags on
5 impact, thereby providing "acceleration de-amplification" for the movement of the passengers on impact.

6 Yet another embodiment has proactive sensors deploying the internal airbags directly,
7 without the installation of external airbags.

8 Yet another embodiment of the invention has a retracting canopy stored in the roof of the
9 vehicle, and attachable to the protector shield or attached components such as the side window, when desired.
10 When attached, the canopy will deploy over the seats when in the extended or loading positions, thereby
11 protecting the seat and the passenger from rain or other snow while entering or leaving the vehicle.

12 Yet another embodiment has external airbags constructed using the Passive Air-Cushion
13 System with micro chambers that are connected to each other by restricted paths that provide visco elastic
14 energy absorbtion in the event of some sections of the airbag being impacted while others are not, thereby
15 forcing air from the compressed micro chambers to the other micro chambers, each of the micro chambers
16 functioning as either a sacrificial chamber or a Micro Air Cushion on impact. This embodiment may of course
17 have external airbags proactively deployed in the manner described herein, prior to impact and their
18 performance as Micro Air Cushion systems. Yet another variation may include one-way valves between the
19 chamber directly connected to the inflation source and each of the micro-chambers (implementable for example
20 with flaps against an aperture) so that inflation may be achieved rapidly, and then the Passive Air-cushion
21 benefits realized on impact.

22 Yet another embodiment uses the Passive Air-cushion system to protect passengers from
23 "Whip Lash" injury, by providing Micro Air-cushions in the vicinity of the head and neck, and providing
24 sacrificial chambers that are compressed in the event of a rear end collision. In some embodiments the sacrificial
25 chamber can be mounted below the seat with one face mounted to the vehicle structure and the other face
26 mounted to the seat of the passenger, the seat being mounted to the support structure to allow controlled limited
27 rearward movement relative to its mountings to allow compression of the sacrificial chamber by the inertial
28 mass of the passenger and seat on impact.

29 Yet another embodiment utilizes multiple adjoining but sepearte Passive Air-cushion
30 systems where on esuch system connects the external airbags (sacrificial chambers) with internal airbags (micro
31 Air-cushions), and another such system connects different and distinct internal airbags (sacrificial chambers) to
32 micro Air-cushions in the vicinity of the passenger's body, thereby creating a cascading system of Passive Air -
33 cushion systems. These embodiments may of course have external airbags proactively deployed in the manner
34 described herein, prior to impact and their performance as Micro Air Cushion systems..

35 Yet another embodiment utilizes an auxiliary brake attached to the secondary slides in
36 addition to the friction limited sliding arrangements of the secondary slide, to provide a further control on the
37 rate of movement of the secondary slide under side or lateral impact.
38

Yet another embodiment utilizes a foot safety switch attached to the foot rest, that activates the sliding mechanism to move the sliding seats into and out of the vehicle. The foot rest in some such embodiments may be bar that is depressed to move the slide into and out of the vehicle. These foot rests being designed to avoid ankle injuries in the event of rear collisions sustained by the vehicle.

Yet another embodiment uses supplementary porous filling materials within prefilled internal airbags designed with suitable vents to change the compression characteristics of the inside airbags under impact.

Yet another embodiment utilizes pressure memory capable materials on the surface of the seats or passenger supports so that surround seats contour to the exact shape of the body for further comfort of passengers and also better support under collision conditions.

Yet another embodiment, has wheel chairs as passenger support mechanisms for the disabled, with collapsible wheels such that the chairs may be backed into clamps that attach on the lower side of the chair supports. In some such embodiments (as illustrated in figures 18A to 18J) these clamps along with the lower cushion of the car seat 148 - (which is specially made to accommodate the chair support cross members), are extended forward on tertiary slides or extension arms with hydraulic automation, such that the movement forward and if necessary down, supports the wheel chair by locking the chair clamps 149 to the chair cross supports 150, and then providing adequate support for the passenger and the wheel chair. The Tertiary Slides or extension arm are supported by the impact decoupler/ Secondary Slides which are in turn attached to the Upper Primary Slides in the extended or loading position. Figure 18B illustrates the position of the seat bottom and clamps just below the wheel chair prior to attachment to the wheel chair. Once the hydraulic mechanism raises the wheel chair off the ground, the Primary Pivot of the rear wheels 151 may be unlocked and the wheel swung up backwards and locked as noted in Figure 18C. Notably the Rear wheels support much of the passenger weight when the wheel chair is used and therefore in addition to the pivoting Principal Rear Wheel Support 152 the rear wheel in addition has a Rear Wheel Support Strut 153 that supports the compressive load when the wheel chair is operational. Thereafter the front wheels may be unlocked and swung back on the Primary Pivots for the Front Wheel 157. This is illustrated in Figure 18D.

Thereafter the space below the wheel chair is clear and the tertiary slide or a mechanism can move the wheel chair back and lock it with and against the Seatback 156 which is shaped to accommodate the cross support members of the wheel chair. This is illustrated in Figure 18E. Such embodiments may have the option to release the rigid back support mounting of the wheel chair 15' thereby benefit from the reclining options of the vehicle seat back. In the process of moving back to back 156, the spring loaded locking sleeves 155, that support the Secondary pivot for rear wheel retraction are pushed forward relative to the wheel chair body thereby releasing the Secondary Pivot for retraction 154 to allow the wheels to swing in and lock behind the seat back 156. This is illustrated in Figure 18F. The wheel chair is then in a position on the extended impact decoupler/secondary slide to be into the vehicle. Notably in this wheel chair conversion embodiment, supplementary side and back airbags may be inflated to fill in the areas where wheel chair support members are in the vicinity of the vehicle also to hold the wheel chair structure securely, thereby providing further protection in the event of a collision. This wheel chair conversion embodiment has all the side impact protection as the

Yet another embodiment utilizes a foot safety switch attached to the foot rest, that activates the sliding mechanism to move the sliding seats into and out of the vehicle. The foot rest in some such embodiments may be bar that is depressed to move the slide into and out of the vehicle. These foot rests being designed to avoid ankle injuries in the event of rear collisions sustained by the vehicle.

Yet another embodiment uses supplementary porous filling materials within prefilled internal airbags designed with suitable vents to change the compression characteristics of the inside airbags under impact.

Yet another embodiment utilizes pressure memory capable materials on the surface of the seats or passenger supports so that surround seats contour to the exact shape of the body for further comfort of passengers and also better support under collision conditions.

Yet another embodiment, has wheel chairs as passenger support mechanisms for the disabled, with collapsible wheels such that the chairs may be backed into clamps that attach on the lower side of the chair supports. In some such embodiments (as illustrated in figures 18A to 18 J) these clamps along with the lower cushion of the car seat 148 – (which is specially made to accommodate the chair support cross members), are extended forward on tertiary slides or extension arms with hydraulic automation, such that the movement forward and if necessary down, supports the wheel chair by locking the chair clamps 149 to the chair cross supports 150, and then providing adequate support for the passenger and the wheel chair. The Tertiary Slides or extension arm are supported by the impact decoupler/ Secondary Slides which are in turn attached to the Upper Primary Slides in the extended or loading position. Figure 18B illustrates the position of the seat bottom and clamps just below the wheel chair prior to attachment to the wheel chair. Once the hydraulic mechanism raises the wheel chair off the ground, the Primary Pivot of the rear wheels 151 may be unlocked and the wheel swung up backwards and locked as noted in Figure 18C. Notably the Rear wheels support much of the passenger weight when the wheel chair is used and therefore in addition to the pivoting Principal Rear Wheel Support 152 the rear wheel in addition has a Rear Wheel Support Strut 153 that supports the compressive load when the wheel chair is operational. Thereafter the front wheels may be unlocked and swung back on the Primary Pivots for the Front Wheel 157. This is illustrated in Figure 18 D.

Thereafter the space below the wheel chair is clear and the tertiary slide or arm mechanism can move the wheel chair back and lock it with and against the Seatback 156 which is specially shaped to accommodate the cross support members of the wheel chair. This is illustrated in Figure 18 E. Some such embodiments may have the option to release the rigid back support mounting of the wheel chair 158, and thereby benefit from the reclining options of the vehicle seat back. In the process of moving back to the seat back 156, the spring loaded locking sleeves 155, that support the Secondary pivot for rear wheel retraction 144 are pushed forward relative to the wheel chair body thereby releasing the Secondary Pivot for rear wheel retraction 154 to allow the wheels to swing in and lock behind the seat back 156. This is illustrated in Figure 18F. The wheel chair is then in a position on the extended impact decoupler/secondary slide to be transported into the vehicle. Notably in this wheel chair conversion embodiment, supplementary side and back air cushions may be inflated to fill in the areas where wheel chair support members are in the vicinity of the passenger and also to hold the wheel chair structure securely, thereby providing further protection in the event of a collision of the vehicle. This wheel chair conversion embodiment has all the side impact protection as the regular seat and

has all the optionality for front impact protection of the safety shield/harness or more conventional options. Figure 18 G shows a plan view of the wheel chair prior to the insertion of Seat lower cushion and support structure. Figure 18 H illustrates an elevation view of the wheel chair and the seat lower cushion and support structure. Still other of these embodiments may use turn tables or other rotating mechanisms rather than the tertiary sliding arrangements or extending arms so that the wheel chair may be directly loaded on a turn table mounted on the impact decoupler/secondary slides, and then rotated into a driving or passenger position when retracted into the vehicle.

Yet another embodiment has anatomical micro-aircushions on the left and right edges of the support surface of the safety shield connected to selected sacrificial chambers along the bottom edge of said support surface. This will provide additional support for the passenger in a side impact, by assisting in preventing body movement outside the countoured seat under collision conditions.

Yet another embodiment has anatomical micro-aircushions on the outer edges of each of the countoured seats, particularly to cover a part of the front of the shoulders the legs and torso in the event of a side collision. These anatomical air-cushions use sacrificial chambers on the sides of the seats.

Yet another embodiment minimizes ejection hazards by controlling further the lateral movement of the seats under side impact. In these embodiments, the Upper primary slide is connected to the locking mechanisms that hold it to the vehicle under operating conditions through shock absorbers or spring mechanisms that allow controlled movement of the upper primary slides out of the vehicle when the vehicle sustains a side impact from the far side. In such embodiments the locks do not disengage when there is a side impact, as the shock absorbing devices provide the required controlled lateral movement of the far side upper primary slide under impact.

Yet another embodiment has a flexible stretchable (or folded) material that is bound to the protector shield and the “doors” of the vehicle on one of its edges where it makes contact normally with the vehicle body, the other edge of the flexible and stretchable material is bound to a frame that locks to the vehicle body under operating conditions. Under normal egress and ingress the frame along with the “doors” with the flexible, stretchable material operates as one unit the frame being held together with the “door” with door impact decouplers that fracture or disengage under impact, thereby allowing the “door” and the upper primary slide on the far side to extend out of the vehicle while the frame remains locked to the vehicle, and stretching the flexible, stretchable material so that passenger body extremities are not ejected from the vehicle but are retained by the flexible stretchable material within the vehicle.

Yet another embodiment has preinflated inside airbags that are deflated when seats move outwards (on the far side) under impact, thereby creating more space within the vehicle, minimizing the need for ejection on the far side under impact.

CONCLUSIONS, RAMIFICATIONS & SCOPE

Thus it will become apparent that the present invention presented, provides a new paradigm for implementing key safety features and providing utility in accessing passenger vehicles and comfort in travelling in such vehicles. While the above description provides many specificities, these should not

1 be construed as limitations on the scope of the present invention, but rather as an exemplification of the
2 preferred, an additional and an alternative embodiment thereof. Many other variations are possible.

3 The present invention provides an arrangement that diverts the impact energy in impacts
4 away from the passengers to the remaining mass of the vehicle thereby protecting the passengers but
5 decelerating the impacting object with the remaining mass of the vehicle. Moreover the arrangement
6 synergistically provides a means for utilitarian easy access to the vehicle for passengers and drivers alike and
7 allows the installation of multi-element surround contoured seats for the comfort and protection of passengers.
8 Furthermore, the arrangement allows the installation of a new and unique safety harness that may obviate the
9 need for safety belts and front impact airbags for protection in head-on collisions. This arrangement differs
10 sharply from the Background art in that it does not simply offer to the impacting body a reinforced rigid shell
11 where the passenger is treated as part of this integral unit, but rather provides selective and differential treatment
12 of the mass of the passengers and driver of the vehicle vis-à-vis the remaining mass of the vehicle. Furthermore
13 the present invention differs sharply from the Background art in that the resulting structure synergistically
14 permits the installation of contoured multi-element surround seats that would not be implementable without the
15 slide arrangements on either side of the vehicle in the present invention.

16 The present invention provides a gravity slide drive for my arrangement for which there is
17 no counterpart in the Background art. This allows further Utility and weight and energy saving in implementing
18 the above elements of the present invention.

19 The present invention includes External side Airbags that differ sharply from the
20 Background art in that for the first time they proactively create a “Just in Time” deceleration zone for the lateral
21 or side impact with internal and/or external side airbags while not remaining in an extended position under
22 normal operating conditions of the vehicle.

23 The present invention describes an indo-skeletal structure of the vehicle body that permits
24 the energy transfer from the lateral or side impact through compressive members to the body of the vehicle.
25 Unlike the Background art this indo-skeletal structure is designed to transfer energy to the body of the vehicle
26 without transferring it to the passengers and driver of the vehicle. The passengers are targeted for protection
27 with “Safety zones”.
28